



DURAVAR® Dowelled Rod Stock

Ultra-High Molecular Weight Polyethylene

PRODUCT CODE	DIAMETER NOMINAL	WEIGHT LBS./FT.	DOWELLED STANDARD TOLERANCE	DOWELLED PREMIUM TOLERANCE	DOWELLED CONCENTRICITY TOLERANCE
RD-106D	1"	.35	(+/-) .010"	(+/-) .005"	(+/-) .003"
RD-107D	1-1/8"	.42	(+/-) .010"	(+/-) .005"	(+/-) .003"
RD-108D	1-1/4"	.54	(+/-) .010"	(+/-) .005"	(+/-) .003"
RD-109D	1-3/8"	.63	(+/-) .010"	(+/-) .005"	(+/-) .003"
RD-110D	1-1/2"	.80	(+/-) .010"	(+/-) .005"	(+/-) .003"
RD-112D	1-3/4"	1.05	(+/-) .010"	(+/-) .005"	(+/-) .003"
RD-114D	2"	1.38	(+/-) .010"	(+/-) .005"	N/A
RD-116D	2-1/4"	1.73	(+/-) .010"	(+/-) .005"	N/A
RD-117D	2-3/8"	1.85	(+/-) .010"	(+/-) .005"	N/A
RD-118D	2-1/2"	2.06	(+/-) .010"	(+/-) .005"	N/A
RD-120D	2-3/4"	2.56	(+/-) .010"	N/A	N/A
RD-122D	3"	3.13	(+/-) .010"	N/A	N/A

- Formulations : Virgin Natural & Virgin Color
Reprocessed Blends
Enhanced Formulations
- Colors : All Standard Colors Meet FDA Requirements
Custom Color Matching Available
- Lengths : Standard = 120" Lengths
Custom = Up To 20 ft. Lengths
- Notation : Duravar Dowelled Rod Stock is machined to close diameter tolerances with excellent roundness. Artek's Dowelled Rod Stock offers excellent surface finish, which reduces the need to perform a secondary finishing process.

